

Product data sheet

Specifications



Battery Breaker Kit, 630A, one circuit breaker for Easy UPS 3M/3L

E3MBBK100K200H

Overview

Presentation	Battery breaker kit that controls DC voltage sent from third party battery solutions to the UPS.
Lead Time	Usually Ships within 6 Weeks

Main

Battery Type	VRLA
Provided Equipment	Installation guide

Batteries & Runtime

Number Of Battery Free Slots	0
Number Of Battery Filled Slots	0
Device Mounting	Enclosed battery cabinet
Battery Power In Vah	0 VAh

Physical

Height	53 cm
Width	32 cm
Depth	23 cm
Net Weight	13 kg
Mounting Mode	Not rack-mountable

Environmental

Ambient Air Temperature For Operation	0...40 °C
Operating Altitude	0...4921 ft
Relative Humidity	0...95 % non-condensing

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	80 cm
Package 1 Width	57 cm
Package 1 Length	50 cm
Package 1 Weight	29 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

✔ Toxic Heavy Metal Free

✔ Mercury Free

✔ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information
