

# Product data sheet

Specifications



## Easy UPS 3M 60kVA 400V 3:3 UPS for external batteries, Start-up 5x8

E3MUPS60KHS

### Overview

**Presentation** Easy-to-install, easy-to-connect, easy-to-use, and easy-to-service 60 kVA 3 phase UPS with advanced product features, robust electrical specifications and compact design making your business continuity easy. Ideal for small and medium data centers and other business critical applications, this UPS is EcoStruxure-ready to give you peace of mind with cloud-based remote monitoring and management. It is supplied without batteries, so you can easily customize your battery solution. Includes 5x8 start-up service.

**Lead Time** Usually Ships within 6 Weeks

### Main

**Main Input Voltage** 400 V 3 phases

**Other Input Voltage** 380 V  
415 V

**Main Output Voltage** 400 V 3 phases

**Other Output Voltage** 380 V  
415 V

**Rated Power In W** 60 kW

**Rated Power In Va** 60 kVA

**Provided Equipment** Dust filter  
Installation guide  
Start-up service

### Batteries & Runtime

**Efficiency** [View Efficiency Graph](#)

**Battery Type** External battery system

### Physical

**Colour** White (RAL 9003)

**Height** 91.5 cm

**Width** 36 cm

**Depth** 85 cm

**Net Weight** 109 kg

**Usb Compatible** Yes

### Input

**Maximum Input Current** 104 A

**Max Short Time Withstand Current** 10 kA

<b>Input Harmonic Distortion</b>	Less than 3 % for full load
<b>Load Power Factor</b>	0.5 leading to 0.5 lagging
<b>Input Power Factor At Full Load</b>	0.99
<b>Input Voltage Limits</b>	342...477 V
<b>Number Of Input Connectors</b>	1 hard wire 5-wire (3P + N + E)
<b>Network Frequency</b>	40...70 Hz

## Output

<b>Maximum Configurable Power In Va</b>	60 kVA
<b>Maximum Configurable Power In W</b>	60 kW
<b>Output Frequency</b>	50 Hz sync to mains 60 Hz sync to mains
<b>Harmonic Distortion</b>	Less than 3 %
<b>Output Harmonic Distortion</b>	< 3% linear load and < 5% non-linear load
<b>Output Overload Operation</b>	10 minutes at 125% and 60 seconds at 150%
<b>Ups Type</b>	Double conversion online
<b>Wave Type</b>	Sine wave
<b>Bypass Type</b>	Built-in static bypass
<b>Crest Factor</b>	3 : 1

## Environmental

<b>Ambient Air Temperature For Operation</b>	0...40 °C
<b>Relative Humidity</b>	0...95 % non-condensing
<b>Operating Altitude</b>	0...4921 ft
<b>Ambient Air Temperature For Storage</b>	-25...55 °C
<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Storage Altitude</b>	0.00...15240.00 m
<b>Acoustic Level</b>	65 dBA
<b>Heat Dissipation</b>	10523 Btu/h
<b>Ip Degree Of Protection</b>	IP20

## Communications & Management

<b>Free Slots</b>	1
<b>Control Panel</b>	Touch screen LCD user interface

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	114 cm
<b>Package 1 Width</b>	96.5 cm
<b>Package 1 Length</b>	47.5 cm
<b>Package 1 Weight</b>	133 kg

# Contractual warranty

---

Warranty

1 year on-site repair or replace with factory authorized Start-Up

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

## Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)